

KR20C

YewdaleKestrel® Crank control

yewdaleKestrel®
MAGNETIC ANTI-LIGATURE SYSTEM



KR20C Crank control

Features:

The YewdaleKestrel® KR20C crank control roller blind features a 45mm grooved aluminium barrel and white metal universal brackets for face or top fixing. A robust 1:5 crank mechanism ensures smooth blind control, and incorporates a magnetic detachable crank handle. Fabric is locked into a groove in the barrel, and features a white Tear Drop aluminium bottom bar as standard. This system uses magnetic wall-fix/top-fix brackets. This ensures that, under excess load, the back bar separates from the bracket leaving no remaining points of ligature.

Benefits:

Durability and simplicity make the KR20C a good choice for a vast range of applications. The magnetic detachable crank ensures the blind is vandal resistant and safe for areas where cords are a threat. Fabric locked into the barrel and bottom bar, supported by sturdy, attractive metal brackets and fitted to white aluminium back bar, secured by magnetic brackets for 100% fail-safe* anti-ligature functionality.

Options:

Bracket covers; Alternative bottom bars including fully fabric covered in aluminium or plastic, and aluminium Tear Drop in black or silver; Fixed crank handle.

Specification:

The magnetic anti-ligature YewdaleKestrel® KR20C crank control roller blind with magnetic detachable crank handle as manufactured by Yewdale, +44 (0)1268 570900. Flame retardant fabric from the YewdaleDefiant® range, locked into grooved 45mm aluminium barrel along with white Tear Drop aluminium bottom bar. Robust vandal resistant 1:5 crank mechanism with pin end supported by white metal brackets and fitted to white aluminium back bar, secured by magnetic wall-fix/top-fix brackets spaced in accordance with manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

YewdaleKestrel® KR20C is the only approved crank control roller blind system to be used with YewdaleKestrel®



For more information on installations, using the systems safely, load testing and maintenance, please scan the QR code to read our YewdaleKestrel® Policy.

Roller Blinds Specification Guide

Roller blinds	Min Width*	Max Width	Max Drop	Max M ²
KR20C	200	2050	3300	5.0

Based on fabric weight of 220g/m², e.g. Thames. Sizes shown in millimetres unless otherwise specified. Use of heavier fabrics may require appropriate reductions. Where adjacent YewdaleKestrel® blinds are fitted, there should be no more than 2 brackets within a total distance of 700mm.



Find this product on
NBS Source



yewdale.co.uk
see things differently

Call: +44 (0)1268 570900 Fax: +44 (0)1268 732509 Email: sales@yewdale.co.uk
Yewdale, Enterprise Way, Wickford, Essex, SS11 8DH | 4 Sutton Lane, London, EC1M 5PU