

# KR20S

YewdaleKestrel® Slow-rise spring

yewdaleKestrel®  
MAGNETIC ANTI-LIGATURE SYSTEM



## KR20S Slow-rise spring

### Features:

The YewdaleKestrel® KR20S spring roller blind with a brake to ensure a slow, smooth and quiet operation. White metal universal brackets fitted to white aluminium back bar for face, top or side fixing with 32mm grooved aluminium barrel. Fabric is locked into a groove in the barrel, and features a white tear drop aluminium bottom bar with cord pull as standard. This system uses magnetic wall-fix/top-fix brackets. This ensures that, under excess load, the back bar separates from the bracket leaving no remaining points of ligature.

### Benefits:

Smooth and quiet operation makes the KR20S an excellent choice for a vast range of applications. The KR20S braked spring blind provides the ultimate cord/chain-free solution and offers exceptional ease of use. The slow-rise spring is enclosed within the barrel and supported by sturdy, attractive metal brackets. Fitted to white aluminium back bar and secured by magnetic brackets for 100% fail-safe\* anti-ligature functionality. Fabric is locked into the barrel and bottom bar maintaining exceptional edge to edge coverage for even better shading properties.

### Options:

Spring limit stop; Alternative bottom bars, including fully fabric covered, in aluminium or plastic, and aluminium Tear Drop in black or silver.

### Specification:

The magnetic anti-ligature YewdaleKestrel® KR20S braked spring control roller blind with vandal resistant, cord/chain-free braked spring as manufactured by Yewdale, +44 (0)1268 570900. Flame retardant fabric from the YewdaleDefiant® range, locked into grooved 32mm aluminium barrel along with white Tear Drop aluminium bottom bar. Slow-rise spring and braked spring end housed within aluminium barrel supported by white metal brackets, and fitted to white aluminium back bar, secured by magnetic wall-fix/top-fix brackets spaced in accordance with manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

**YewdaleKestrel® KR20S is the only approved braked spring roller blind system to be used with YewdaleKestrel®**



For more information on installations, using the systems safely, load testing and maintenance, please scan the QR code to read our YewdaleKestrel® Policy.

## Roller Blinds Specification Guide

Roller blinds	Min Width*	Max Width	Max Drop	Max M <sup>2</sup>
KR20S**	450	1850	2450	4.3

Sizes shown in millimetres. Based on fabric weight of 220g/m<sup>2</sup>, e.g. Thames. Use of heavier fabrics may require appropriate reductions. \*Where adjacent blinds are fitted with YewdaleKestrel®, there should be no more than 2 brackets within a total distance of 700mm.

\*\*Use of limit stop may require appropriate reductions.



Find this product on  
NBS Source



yewdale.co.uk  
see things differently

Call: +44 (0)1268 570900 Fax: +44 (0)1268 732509 Email: sales@yewdale.co.uk  
Yewdale, Enterprise Way, Wickford, Essex, SS11 8DH | 4 Sutton Lane, London, EC1M 5PU